

FILTRATION CENTRIFUGE SIEVA-3



HERMLE
LABORTECHNIK



Description

- Maintenance free induction drive
- Microprocessor controlled speed regulation
- Speed pre-selection from 200 rpm up to 10,000 rpm in increments of 10 rpm
- Running time pre-selection from 10 sec. to 99 h 59 min. in increments of 10 sec. or continuous run
- Imbalance switch-off
- Automatic lid-lock
- Transparent centrifuge lid for visual control
- Stainless steel chamber and housing parts
- Quick key for short runs
- CE-conformity
- Manufactured according to international safety regulations, i.e IEC 61010 and 61010-2

Centrifugal Baskets 500 ml



**Order No.: 221.07 V02
perforated**



**Order No.: 221.07 V04
not perforated**



**Order No.: 221.07 V06
perforated
incl. special coating „SafeCode 778“**

Filter material PP DWL

- Order No. 25-7100: pore size 7 μ
- Order No. 25-7101: pore size 20 μ
- Order No. 25-7102: pore size 30 μ
- Order No. 25-7103: pore size 50 μ



**Rotor incl.
filter material**



**Package unit with
10 filter each!**

Technical Data

- Speed max.: 10,000 rpm
- RCF max.: 7,825 xg
- Acceleration time: 9 sec.
- Deceleration time: 12 sec.
- Current supply: 230 V / 120 V
- Power supply: 0.85 KW

Dimensions

- W x H x D: 38 x 32 x 50 cm
- Weight: approx. 37 kg
(Unit V01/V02)

- Weight: approx. 43 kg
(Unit V03/V04/V05)

SIEVA-3 Units

- Order No.: 330.00 V01 - 230 V / 50-60 Hz
- Order No.: 330.00 V02 - 120 V / 50-60 Hz

- Order No.: 330.00 V03 - 230 V / 50-60 Hz
for external temperature equalization
- Order No.: 330.00 V04 - 120 V / 50-60 Hz
for external temperature equalization

- Order No.: 330.00 V05 - 230 V / 50-60 Hz
for external temperature equalization
incl. special coating „SafeCoat 778“
incl. USB-package 800.001



- Connection for external
temperature equalization

HERMLE

LABORTECHNIK

HERMLE Labortechnik GmbH
Siemensstr. 25
78564 Wehingen
Telefon: +49 - 74 26 - 96 22-0
Telefax: +49 - 74 26 - 96 22-49
E-mail: info@hermleLT.de
Internet: <http://www.hermle-labortechnik.de>